

## DRACO® BAND 100

### ELASTIC WATERPROOFING SEALING REINFORCEMENT STRIP

---

#### Description

DRACO® BAND 100 is a waterproofing sealing reinforcement strip. It is highly elastic in transversal direction and less elastic in longitudinal direction. It consists of sealing band made of thermoplastic elastomer integrated with polypropylene fabric.

---

#### Advantages

- Simple application.
- Significant elongation in transversal direction and tensile strength.
- Compatible with all building materials.

---

#### Fields of application

- For sealing of working joints, connections and cracks in buildings.
- For reinforcement of waterproofing coatings over working joints, on connections of surfaces, under ceramic tiles or stone pavement, in bathrooms, showers, on terraces, balconies and roofs.
- For reinforcement of waterproofing coating systems.

---

#### Surface preparation

- Surface must be clean, without grease, dust or frost. Any damaged areas must be repaired and cleaned.

---

#### Application

- Apply first layer of binder (glue, mortar) or waterproofing coating. Apply DRACO® BAND 100 in the first layer of coating (binder) with a spatula, trowel or scraper, making sure it is fully saturated and without wrinkles. Make sure that the sealing side of the tape, covered with polyester fabric, is facing you. At the corners and around penetrations use additional elements. Cover the tape with second layer of coating (binder) completely.

---

#### Physical and technical specifications

CHARACTERISTIC	PERFORMANCE
Sealing width:	7,0 cm
Total width:	12,0 cm
Thickness:	0,70 mm
Tensile strength (MD/CMD):	120,0/58,0 N/50 mm
Elongation at break (MD/CMD):	37/126 %
Water impermeability:	1,5 bar

---

**Safety and storage**

- DRACO® BAND 100 and additional elements are non-toxic products. Store them in closed place.

---

**Packaging**

- Rolls 10,0 m long and 12,0 cm wide.
-