

DRACO® PRIMO 600

SINGLE-COMPONENT PRIMER FOR NON-POROUS SUBGRADES

Description

DRACO® PRIMO 600 is a single-component colourless primer created to ensure adhesion of waterproofing coating DRACO® GARD 600 against non-porous subgrades. Although created for DRACO® GARD 600 it is suitable for range of all DRACO® GARD products.

DRACO® PRIMO 600 consists of organosilan, that reacts with humidity, in mixture of solvent and additives to ensure complete surface covering. It dries quickly, within 10 – 15 minutes, when the subgrade is prepared for application of waterproofing coating.

Advantages

- Simple application. Single component.
- Very fast curing.
- No thinning is required.
- It doesn't change surface appearance.

Fields of application

- As primer for non – porous substrates (tiles and glass).
- As primer for slightly porous marble.

Surface preparation

- Clean the surface thoroughly, if it is possible use water under pressure. Remove oil, grease and wax contaminants.

Application

- Shake and apply DRACO® PRIMO 600, on a clean, dry and firm surface, with a clean cloth like You are sweeping it. After 10 – 15 minutes apply DRACO® GARD 600.

Physical and technical specifications

CHARACTERISTIC OF LIQUID COAT	PERFORMANCE	METHOD
Viscosity (BROOKFIELD):	40 cP	ASTM D2196-86 at 25°C
Specific weight:	0,83 g/cm ³	ASTM D1475 / DIN 53217
Flash point:	42°C	ISO 2811 at 20°C
Drying time to become tacky at 25 C and 55% of relative air humidity:	10 – 15 min.	ASTM D93, closed container
		-

Consumption

- Depending on subgrade porosity (min. 100 g/m²).

Safety and storage

- DRACO® PRIMO 600 can be kept for 12 months minimum in the original unopened pails in dry places and at temperatures of 5°C - 25°C.
- Once opened, use as soon as possible.

Warnings

- DRACO® PRIMO 600 is an easily flammable liquid that can irritate the skin, eyes and the respiratory system. Use only in the open air or in a well-ventilated area.
- The user must check the suitability of the product for the intended use and purpose of the product.
- All the physical and technical specifications listed in this Technical Data Sheet are based on laboratory tests.
- Data and recommendations related to the application and end-use of DRACO products are given in good faith based on DRACO's current knowledge and experience for products that are properly stored and used in accordance with DRACO guidelines.

Limitations

- Apply minimum quantity of product using clean cloth.
- Avoid formation of small ponds.

Packaging

- Cans of 1,0 l and 5,0 l.
-